

SPC Floorings


Elevate Your Space with SPC!




Brand By
CASA DESIGNO

OUR ADVANTAGES

WHY **DICHA** SPC FLOORINGS?




**Impact
Resistant**




**Fire
Resistant**




**Termite
Proof**




**Anti-
Skid**



**Water
Proof**



**Stain
Resistant**



**Scratch
Resistant**



**Glue Less
Installation**

1220 x 181 x 5mm

23.77 sqft / box

REAL CDSP 501



SPC Floorings



1220 x 181 x 5mm

23.77 sqft / box

HAZEL CDSP 502



SPC Floorings



1220 x 181 x 5mm

23.77 sqft / box

ANTIQUE CDSP 503



SPC Floorings



1220 x 181 x 5mm

23.77 sqft / box

BEAM CDSP 504



SPC Floorings



1220 x 181 x 5mm

23.77 sqft / box

NEUTRAL CDSP 505



SPC Floorings



1220 x 181 x 5mm

23.77 sqft / box

ROBEL CDSP 506



SPC Floorings



1220 x 181 x 5mm

23.77 sqft / box

MODERN CDSP 507



SPC Floorings




Dicha
Crafting Dreams

1220 x 181 x 5mm

23.77 sqft / box

MURKEY CDSP 508



SPC Floorings


Dicha
Crafting Dreams

SPC Flooring Technical Data

CHARACTERISTICS	STANDARDS			
	EN	Result	ASTM	Result
Size	EN 427	Pass	ASTM F536	Pass
Overall Thickness	EN 428	Pass	ASTM F36	Pass
Wear Layer Thickness	EN 429	Pass	ASTM F410	Pass
Dimension Squareness and Straightness	EN 427	Pass Squareness:0.18mm Straightness:0.07mm		
Chemical Resistance	EN 423	Pass	ASTM F925, ASTM F1344	Pass
Colour Fastness to Artificial Light	EN20105:B02 Method A	Pass, >Grade 6	ASTM F1515	Pass
Heat Stability by Color Change			ASTM F1514	Pass
Castor Chair Suitability	EN 425	Pass		
Residual Indentation	EN 433	Pass, 0.06mm	ASTM F1914, ASTM F970	Pass
Abrasion Group	EN 660-1/2	Group T	ASTM F510, ASTM D3384	Pass
Impact Resistance			ASTM F1265, ASTM D2632	Pass
Dimensional Stability	EN 434	Pass	ASTM F2199	Pass, 0.1%
Sound Resuction	ENIS0717-2(ΔLw)	2 dB		
Flexibility	EN 435 Method A	Pass	ASTM F137	Pass
Slip Resistance	EN 13893	Class DS	ASTMD2047-93	Pass
Electrical Resistance	EN 1081 Method C	Pass	ASTM F150-06	Pass
Thermal Resistance	EN 12664	Pass		
Toxic Element Test	EN 71-3	Pass. Not toxic. Does not Contain heavy metal and formaldehyde		
Behaviour to Fire	ENIS011925-2 ENI3501-1 EN ISO 9239-1	Bf1-S1	ASTM E648-06	Pass/Class1
Smoke Density			ASTM E662	Pass,<450





SPC Floorings

Brand By:



Contact Us:

Casa Designo International

Khasra Number 162/2 & 245, Village Bhartal, Near Holi Chowk,
New Delhi – 110 077

☎ +91 97739 80501

✉ sales@casadesigno.com